



TM

LEGENDARY  
LIGHTING®





ATLAS



VULCAN



STATE STREET





# LEGENDARY LIGHTING®

Established in 1999, Legendary Lighting is a manufacturer of copper gas and electric lanterns that are hand built at our facility in Flowood, Mississippi.

Legendary Lighting strives to handcraft an exceptional lighting product that will not only meet the needs of traditional or contemporary architecture but surpass quality and design standards while remaining economically feasible.

Each Legendary Lighting collection possesses its own exceptional design and beauty that helps to bring a timeless ambiance to any project while fulfilling the demand for a quick lead time, cost efficiency and excellent performance. In addition, all of our lanterns are UL listed and certified to meet the most stringent building codes and are even safe to burn indoors.

Complete customer satisfaction is our goal and we have fulfilled this by creating a product that combines the artistry of fine craftsmanship with an innovative production process to bring forward an adequately priced product without sacrificing excellence.





# ATLAS









AS2-W



WALL MOUNT	H	W	D
AS1-W	27-1/2"	12"	15-11/16"
AS2-W	31"	14"	17-11/16"
AS3-W	40"	18"	22-1/4"





AS2-CWB



AS1-CWB	22-5/16"	12"	14-5/8"
AS2-CWB	25-5/16"	14"	16-1/8"
AS3-CWB	32-7/8"	18"	21"



AS2-P





POST MOUNT	H	W	D
AS1-P	25-9/16"	12"	12"
AS2-P	28-9/16"	14"	14"
AS3-P	36-1/8"	18"	18"



AS2GT-Y

glass top



CEILING MOUNT	H	W	D
AS1-Y	33-13/16"	23-7/8"	14-1/4"
AS2-Y	37-1/4"	25-3/4"	16-1/4"
AS3-Y	44-7/16"	33-3/4"	20-1/4"



# Apollo



LEGENDARY LIGHTING





AO1-W



WALL MOUNT	H	W	D
AO1-W	27-3/4"	16-1/8"	18"
AO2-W	32"	18-7/8"	20-3/8"
AO3-W	38-5/16"	23-15/16"	25"





AO1-CWB



AO1-CWB	21-11/16"	15-7/8"	16-1/2"
AO2-CWB	25-5/16"	18-3/4"	18-7/8"
AO3-CWB	30-1/4"	23-15/16"	23-3/8"





AO1-P



POST MOUNT	H	W	D
AO1-P	25-3/16"	15-7/8"	13-3/4"
AO2-P	28-13/16"	18-3/4"	16-1/4"
AO3-P	33-3/4"	23-15/16"	20-3/4"



AO1-Y



CEILING MOUNT	H	W	D
AO1-Y	35-1/2"	26-11/16"	15"
AO2-Y	39-3/16"	29-1/2"	17-7/16"
AO3-Y	47-9/16"	39-7/16"	22-5/16"





# VULCAN









VN1-W



WALL MOUNT	H	W	D
VN1-W	35-15/16"	8-7/8"	12-7/8"
VN2-W	44"	10-7/8"	14-7/8"
VN3-W	50-9/16"	13"	16-5/8"





VN1-CWB



VN1-CWB	23-1/8"	8-3/4"	11-1/8"
VN2-CWB	27-1/4"	10-3/4"	13-1/8"
VN3-CWB	34-5/8"	13"	15"





VN1-P



POST MOUNT	H	W	D
VN1-P	29-3/8"	8-3/4"	8-3/4"
VN2-P	34-5/8"	10-3/4"	10-3/4"
VN3-P	40-7/8"	13"	13"



VN1-Y



CEILING MOUNT	H	W	D
VN1-Y	37-5/8"	11-9/16"	11"
VN2-Y	42-3/16"	13-9/16"	13"
VN3-Y	50-9/16"	16-3/8"	15-1/2"



# ORACLE









OC1-W



WALL MOUNT	H	W	D
OC1-W	26"	7-1/2"	13-11/16"
OC2-W	30"	9-1/2"	14-11/16"
OC3-W	36"	11"	17-3/16"



OC1-CWB



OC1-CWB	17-1/2"	7-1/2"	10-1/2"
OC2-CWB	21-3/4"	9-1/2"	12-1/2"
OC3-CWB	27-3/8"	11"	14"





OC1-P



POST MOUNT	H	W	D
OC1-P	22-1/4"	7-1/2"	7-1/2"
OC2-P	26-1/2"	9-1/2"	9-1/2"
OC3-P	32-1/8"	11"	11"



OC1-Y



CEILING MOUNT	H	W	D
OC1-Y	31-3/4"	11-9/16"	7-1/2"
OC2-Y	35-7/8"	13-9/16"	9-1/2"
OC3-Y	41-1/2"	16-3/8"	11"



# EQUESTRIAN









EQ1-W



WALL MOUNT	H	W	D
EQ1-W	29"	8-3/4"	12-13/16"
EQ2-W	35-1/4"	10-3/4"	14-3/4"
EQ3-W	42"	13"	16-11/16"





EQ1-CWB



EQ1-CWB	22-5/8"	8-3/4"	11-1/8"
EQ2-CWB	28-1/2"	10-3/4"	13-1/8"
EQ3-CWB	34-3/4"	13"	15"





EQ1-P



POST MOUNT	H	W	D
EQ1-P	27-3/8"	8-3/4"	8-3/4"
EQ2-P	33-1/4"	10-3/4"	10-3/4"
EQ3-P	39-1/2"	13"	13"



EQ1-Y



CEILING MOUNT	H	W	D
EQ1-Y	37-11/16"	11-9/16"	11"
EQ2-Y	42-7/16"	13-9/16"	13"
EQ3-Y	50-1/2"	16-3/8"	15-1/2"



# STATE STREET









SSA1-W



WALL MOUNT	H	W	D
SSA1-W	29-3/16"	12"	15-11/16"
SSA2-W	32-7/16"	14"	17-11/16"
SSA3-W	40-1/8"	18"	22-1/4"





SSA1-CWB



SSA1-CWB	24"	12"	15"
SSA2-CWB	26-3/4"	14"	16-5/8"
SSA3-CWB	33"	18"	20-5/8"





SSA1-P



POST MOUNT	H	W	D
SSA1-P	27-1/4"	12"	12"
SSA2-P	30"	14"	14"
SSA3-P	36-1/8"	18"	18"




SSA1-Y




CEILING MOUNT	H	W	D
SSA1-Y	33-13/16"	23-7/8"	14-1/4"
SSA2-Y	37-5/16"	25-3/4"	16-1/4"
SSA3-Y	44-1/2"	33-3/4"	20-1/4"


# KYRO



WALL MOUNT	H	W	D
KR1-CWB	22"	11"	9-5/8"
KR2-CWB	26-3/8"	15"	11-5/8"
KR3-CWB	32"	19-1/4"	13-5/8"





POST MOUNT	H	W	D
KR1-P	26-13/16"	11"	6-7/8"
KR2-P	31-1/8"	15"	9-1/4"
KR3-P	36-3/4"	19-1/4"	11-1/4"



CEILING MOUNT	H	W	D
KR1-Y	37"	13-9/16"	6-7/8"
KR2-Y	40-5/16"	17-9/16"	9-1/4"
KR3-Y	46-3/16"	22-1/8"	11-1/4"





# NEPTUNE



WALL MOUNT	H	W	D
NE1-CWB	24-3/16"	12-9/16"	13-1/4"
NE2-CWB	27-5/8"	14-1/16"	14-11/16"
NE3-CWB	34-1/16"	18-3/4"	17-3/8"





NE2-CWB



POST MOUNT	H	W	D
NE1-P	28-15/16"	12-9/16"	11"
NE2-P	32-11/16"	14-3/16"	12-7/16"
NE3-P	38-13/16"	18-3/4"	16-1/2"



NE2-P



CEILING MOUNT	H	W	D
NE1-Y	38-3/8"	16-1/8"	12-1/16"
NE2-Y	41-3/4"	17-3/4"	13-1/16"
NE3-Y	48-1/2"	21-7/8"	17-1/16"





NE2-Y

# MINI

electric only





AOM-W



APOLLO MINI	H	W	D
AOM-W	17"	12"	10-7/8"





VNM-W



VULCAN MINI	H	W	D
VNM-W	21-3/8"	6-5/8"	6-1/2"





ASM-W



ATLAS MINI	H	W	D
ASM-W	17"	9"	9-1/4"



OCM-W



ORACLE MINI	H	W	D
OCM-W	13-1/2"	5-5/8"	6-1/8"



# SOURCE



2 BULB CANDELABRA



3 BULB CANDELABRA



EDISON BASE



VORTEX FLAME <sup>[1]</sup> <sup>[2]</sup>



## ELECTRONIC IGNITION

### 3 YEAR WARRANTY

The convenience of our Electronic Ignition system allows the lantern to be turned on and off with the flip of a switch. Electronic Ignition can be operated with a timer, photo electronic cell, dusk to dawn switch, or smart home control system allowing control over burn time. The lantern will also re-light in the event the flame is blown out.

[1] SIZE 11 & 111 ONLY  
[2] NATURAL GAS ONLY


# ACCESSORIES



WALL MOUNT YOKE BRACKET



YOKE EXTENSION




COPPER CHAIN



HALF YOKE WITH ARMS + BALL






LP1 DECORATIVE POST  
SPIDER POST BRACKET  
LADDER REST



COPPER COLLAR  
ON A COLUMN MOUNT BRACKET



SPIDER POST BRACKET  
ON A COLUMN MOUNT BOX



COPPER COLUMN MOUNT BOX


# ACCESSORIES



COPPER TOP CURL



STEEL TOP CURL



BOTTOM SCROLL



COPPER MUSTACHE CURL




STEEL MUSTACHE CURL





SPINNING




ARCH + BALL




SEEDY GLASS


## FINISHES



BLACK



PATINA ANTIQUE



GERMAN ANTIQUE



PATINA GREEN





# LEGENDARY LIGHTING<sup>®</sup>

LIMITED LIABILITY COMPANY



All of our lanterns are hand crafted and tested before they leave the factory to ensure the highest safety standards.

Lanterns are constructed of 16, 24, and 32 oz. copper and tempered glass is standard for all gas lanterns.

Size 1 & 2 natural gas lanterns use up to 3,451 BTU per hour. Size 3 natural gas lanterns use up to 4,854 BTU per hour. Size 1 & 2 propane gas lanterns use up to 2,800 BTU per hour. Size 3 propane gas lanterns use up to 4,854 BTU per hour.

All natural gas and propane gas lanterns include a shut-off valve located at the base of the burner. Lanterns made without the electronic ignition option are designed to burn continuously.

All gas, propane, and electric lanterns are UL certified for outdoor or indoor use under NCOG.MH61678 to comply with ANSI Standard Z21.42.

## LEGENDARYLIGHTING.COM

5230 HWY. 25  
FLOWOOD MS 39232  
601-992-9955

